

**THE MUNICIPAL CORPORATION OF THE  
TOWNSHIP OF KILLALOE, HAGARTY AND RICHARDS**

**BY-LAW NO. 35 - 2024**

**Being a by-law to amend By-Law No. 43 – 2016, being a by-law to establish road maintenance standards and road classifications for highways within the jurisdiction of the Township of Killaloe, Hagarty and Richards and delegation to the Public Works Superintendent with respect to temporary road closures;**

**WHEREAS** Sections 27 and 28 of the *Municipal Act, 2001*, S.O. 2001 c.25 and related regulations thereto authorizes a municipality to pass by-laws in respect of highways over which it has jurisdiction;

**AND WHEREAS** the Council for the Township of Killaloe, Hagarty and Richards deems it necessary to pass a by-law amending By-law No. 42 - 2016 respecting the classification and maintenance of highways under its jurisdiction;

**AND WHEREAS** pursuant to Section 42 of the *Municipal Act, 2001*, S.O. 2001 c.25, a municipality may delegate to a committee of council or to an employee of the municipality, subject to any conditions, which the municipality may impose the power to close a highway temporarily of any purpose specified in the by-law;

**NOW THEREFORE** the Council for the Township of Killaloe, Hagarty and Richards enacts as follows:

1. **THAT**, for the purposes of this by-law, "highway" is defined as those roadways that are municipally maintained and as described and classified as set out in Schedule "A", attached hereto and forming part of this by-law.
2. **THAT**, "Class 6" highway standards as outlined in Schedule "B", which is attached hereto and forms part of this by-law.
3. **THAT**, Regulation 239/02, and associated amendments, made under the *Municipal Act 2001*, defining minimum maintenance standards for highways with classifications of 1,2,3,4, and 5, is hereto attached as Schedule "C" and forming part of this by-law.
4. **THAT**, winter maintenance on highways under the jurisdiction of the municipality shall be conducted annually beginning on October 15th and continuing to, and including, April 14th.
5. **THAT**, pursuant to Section 42 of the *Municipal Act, 2001*, S.O. 2001 c.25, Council for the Township of Killaloe, Hagarty and Richards hereby delegates authority to the Public Works Superintendent or in the absence of the Public Works Superintendent the Deputy Public Works Superintendent of the Township of Killaloe, Hagarty and Richards to temporarily close a highway under the jurisdiction of the municipality in the case of emergencies or for maintenance or construction activities determined by the Public Works Superintendent, and for special events as approved by council from time to time.
7. **THAT**, this by-law shall amend by-law 43 – 2016 for the Township of Killaloe, Hagarty and Richards.
8. **THAT**, this by-law shall come into force and take effect upon final passing thereof.

READ A FIRST, SECOND and THIRD TIME and FINALLY PASSED THIS 1st DAY OF OCTOBER 2024.

---

Mayor – Dave Mayville

---

CAO/Clerk-Treasurer – Tammy Gorgerat

**Schedule "A" to By-Law No. 35 - 2024**

<b>Township of Killaloe, Hagarty and Richards</b>		
<b>Road Name</b>	<b>Description</b>	<b>Class</b>
Albert St.		4
Antoine	911 #120 to 911 #314	5
Bear Trail Rd		4
Beaver Rd		5
Beechnut Lake Rd	From Cty Rd. 58 to 911 #68	6(b)
Buck Hill Rd	From Simpson Pit Rd. to 911 #296	5
Buck Hill Rd	From 911 #296 to Horseshoe Rd. intersection	5
Byers Creek Rd	From Simpson Pit Rd. to 911 #287	4
Byers Creek Rd	From 911 #287 to Dead End at 911# 686	6(b)
Cain Rd		6(a)
Cardinal Rd		5
Church St.		4
Deer Trail Rd	From Round Lake to 911 #164	5
Deer Trail Rd	From 911 #164 to 911 #462	5
Division Rd	From Round Lake West to 911 #1863	4
Division Rd	From 911 #1863 to Horseshoe Rd. Intersection 911 #2510	6(a)
Doyle Mountain Rd		4
Eno Rd		4
Foy Park Corridor	From intersection with Red Rock Road to Intersection with County Rd. #58 (Round Lake Road)	4
Gorman Rd		6(a)
Green Ridge Rd	From 911 #55 North to 911 #333	5
Greens Rd	From Brudenell Rd. to 911 #680	5
Harrington Rd		5
Heritage Rd	From Old Trestle Rd. to 911 #1454	5
Hidden Trail Rd		5
High Country Rd		5
Hillcrest Avenue	From Hwy 60 to 911 #106	5
Horseshoe Rd		6(a)
Inukshuk Rd		5
Jack Chute Rd		5
John Street		5
John Foy Lane		5
Lake Street		4
Lakeview Drive		5
Lenny Rd	From Mountain View Rd. to 911 #7	5
Lenny Rd	From 911 #7 to 911 #177	5
Lisk Rd		5
Long Meadow Rd	From Cty Rd. #58 to 911 #296	5
Mask Rd	From Hwy 60 to 911 #2491	4
Mockingbird Rd	From Turners Rd. to 911 #79	5
Mockingbird Rd	From 911 #79 to 911 #179	6(a)
Mountain View Rd		4
O'Grady Settlement Rd		5
Oak Avenue		5
Old Trestle Rd		5
Pecoskie Drive		5
Pine View Drive		5
Red Rock Rd		4
Rink Rd	From Cty Rd. #58 to 911 #43	5
River Rd	From Tramore Rd. to 911 #6527	5

**Schedule "A" to By-Law No. 35 – 2024 – Continued**

River Rd	From 911 #6527 to 911 #6570 Dead End	6(a)
Rochefort Rd		4
Rozek Rd	From Scenic Rd. to 911 #26	5
Rozek Rd	From 911 #26 to 911# 826 Dead End	6(b)
Scenic Rd	From Wilno Rd. North to 911 #1318	5
Scenic Rd	From 911 #1318 to 911 #1398	5
Simpson Pit Rd South		5
Stone Church Rd	From Old Trestle Rd. to 911 #767	4
Stone Church Rd	From 911 #767 to 911 #992	6
Sunrise Rd	From Cty Rd. #58 to 911 #168	5
Sunrise Rd	From 911 #168 to 911 #306	6
Tramore Rd		4
Turners Rd		4
White Church Rd		4
Wildlife Rd	From Cty Rd. 58 West to 911 #596	5
Wildlife Rd	From Hwy 60 to Cty Rd. #58	6(b)
Wilno North Rd	From Scenic Rd to Antoine Rd	5
Winnie Rd	From Intersection with Antoine Rd. to 911 #250	6(b)
Yantha Drive		4

**Streets – Former Village of Killaloe**

<b>Road Name</b>	<b>Description</b>	<b>Class</b>
Angus Street		5
Annie Street		5
Boland Street		5
Cameron Street		5
Civic Street		5
Coll Street		5
Elm Street		5
Henry Street		5
James Street		5
John Street		5
Keetch Street		5
King Street		5
Lake Street		5
Lane Street		5
Lisk Street		5
Maple Street		5
Mary Street		5
Meadow Drive		5
McCarthy Lane		5
Mill Street		4
North Street		5
River Street		5
Roche Street		5
Ryan Street		5
Water Street		5
William Street		5
Zummach Drive		5

**Schedule "B" to By-Law No. 35 - 2024**

**CLASS 6 ROADS**

Class 6 (A)

**Routine Patrolling Frequency**

Once every 60 days

Class 6 (A)

**Snow Accumulation**

Depth - 30 cm

Time – 3 weeks

Class 6 (A)

**Icy Roadways**

2 weeks or 14 days

Class 6 (A & B)

**Potholes on Paved Surface of Roadway**

Surface area            1500 cm<sup>2</sup>

Depth                    10 cm

Time                      90 days

Class 6 (A & B)

**Potholes on Non Paved Surface of Roadway**

Surface area            2000 cm<sup>2</sup>

Depth                    14 cm

Time                      3 months or 90 days

Class 6 (A & B)

**Potholes on Paved or Non Paved Surface of Shoulders**

Surface area            2000 cm<sup>2</sup>

Depth                    14 cm

Time                      3 months or 90 days

Class 6 (A & B)

**Shoulder Drop –offs**

Depth                    14 cm

Time                      3 months or 90 days

Class 6 (A & B)

**Cracks**

Width                    8 cm

Depth                    10 cm

Time                      180 days

Class 6 (A & B)

**Luminaries**

Time                      28 days

Class 6 (A & B)

**Regulating and Warning Signs**

Time                      90 days

**Schedule "B" to By-Law No. 35 – 2024 – Continued**

Class 6 (A & B)

**Bridge Deck Spalls**

Surface area	1500 cm <sup>2</sup>
Depth	10 cm
Time	21 days

Class 6 (A & B)

**Surface Discontinuities**

Height	10 cm
Time	60 days

Class 6 (B)

**Snow Accumulation & Icy Roadways**

Requests for winter maintenance on Class 6(B) roads will be dealt with on "a reasonable request" basis, and will be carried out dependant upon the availability of road equipment and personnel. Requests must be made to the Road Superintendent at least 48 hours prior to the commencement of requested maintenance.

## Schedule "C" to By-Law No. 35 – 2024

### Municipal Act, 2001 Loi de 2001 sur les municipalités ONTARIO REGULATION 239/02

#### MINIMUM MAINTENANCE STANDARDS FOR MUNICIPAL HIGHWAYS

**Consolidation Period:** From May 3, 2018 to the [e-Laws currency date](#).

Last amendment: 366/18.

Legislative History: 288/03, 613/06, 23/10, 47/13, 366/18.

***This Regulation is made in English only.***

#### Definitions

1. (1) In this Regulation,

"bicycle facility" means the on-road and in-boulevard cycling facilities listed in Book 18 of the Ontario Traffic Manual;

"bicycle lane" means,

(a) a portion of a roadway that has been designated by pavement markings or signage for the preferential or exclusive use of cyclists, or

(b) a portion of a roadway that has been designated for the exclusive use of cyclists by signage and a physical or marked buffer;

"cm" means centimetres;

"day" means a 24-hour period;

"encroachment" means anything that is placed, installed, constructed or planted within the highway that was not placed, installed, constructed or planted by the municipality;

"ice" means all kinds of ice, however formed;

"motor vehicle" has the same meaning as in subsection 1 (1) of the *Highway Traffic Act*, except that it does not include a motor assisted bicycle;

"non-paved surface" means a surface that is not a paved surface;

"Ontario Traffic Manual" means the Ontario Traffic Manual published by the Ministry of Transportation, as amended from time to time;

"paved surface" means a surface with a wearing layer or layers of asphalt, concrete or asphalt emulsion;

"pothole" means a hole in the surface of a roadway caused by any means, including wear or subsidence of the road surface or subsurface;

"roadway" has the same meaning as in subsection 1 (1) of the *Highway Traffic Act*;

"shoulder" means the portion of a highway that provides lateral support to the roadway and that may accommodate stopped motor vehicles and emergency use;

"sidewalk" means the part of the highway specifically set aside or commonly understood to be for pedestrian use, typically consisting of a paved surface but does not include crosswalks, medians, boulevards, shoulders or any part of the sidewalk where cleared snow has been deposited;

"significant weather event" means an approaching or occurring weather hazard with the potential to pose a significant danger to users of the highways within a municipality;

"snow accumulation" means the natural accumulation of any of the following that, alone or together, covers more than half a lane width of a roadway:

1. Newly-fallen snow.
2. Wind-blown snow.
3. Slush;

"substantial probability" means a significant likelihood considerably in excess of 51 per cent;

"surface" means the top of a sidewalk, roadway or shoulder;

"utility" includes any air, gas, water, electricity, cable, fiber-optic, telecommunication or traffic control system or subsystem, fire hydrants, sanitary sewers, storm sewers, property bars and survey monuments;

"utility appurtenance" includes maintenance holes and hole covers, water shut-off covers and boxes, valves, fittings, vaults, braces, pipes, pedestals, and any other structures or items that form part of or are an accessory part of any utility;

"weather" means air temperature, wind and precipitation.

"weather hazard" means the weather hazards determined by Environment Canada as meeting the criteria for the issuance of an alert under its Public Weather Alerting Program. O. Reg. 239/02, s. 1 (1); O. Reg. 23/10, s. 1 (1); O. Reg. 47/13, s. 1; O. Reg. 366/18, s. 1 (1, 2).

(2) For the purposes of this Regulation, every highway or part of a highway under the jurisdiction of a municipality in Ontario is classified in the Table to this section as a Class 1, Class 2, Class 3, Class 4, Class 5 or Class 6 highway, based on the speed limit applicable to it and the average daily traffic on it. O. Reg. 239/02, s. 1 (2); O. Reg. 366/18, s. 1 (3).

(3) For the purposes of subsection (2) and the Table to this section, the average daily traffic on a highway or part of a highway under municipal jurisdiction shall be determined,

- (a) by counting and averaging the daily two-way traffic on the highway or part of the highway;  
or
- (b) by estimating the average daily two-way traffic on the highway or part of the highway.  
O. Reg. 239/02, s. 1 (3); O. Reg. 23/10, s. 1 (2); O. Reg. 366/18, s. 1 (3).

(4) For the purposes of this Regulation, unless otherwise indicated in a provision of this Regulation, a municipality is deemed to be aware of a fact if, in the absence of actual knowledge of the fact, circumstances are such that the municipality ought reasonably to be aware of the fact. O. Reg. 366/18, s. 1 (4).

TABLE  
CLASSIFICATION OF HIGHWAYS

Column 1 Average Daily Traffic (number of motor vehicles)	Column 2 91 - 100 km/h speed limit	Column 3 81 - 90 km/h speed limit	Column 4 71 - 80 km/h speed limit	Column 5 61 - 70 km/h speed limit	Column 6 51 - 60 km/h speed limit	Column 7 41 - 50 km/h speed limit	Column 8 1 - 40 km/h speed limit
53,000 or more	1	1	1	1	1	1	1
23,000 - 52,999	1	1	1	1	2	2	2
15,000 - 22,999	1	1	2	2	2	3	3
12,000 - 14,999	1	1	2	2	2	3	3
10,000 - 11,999	1	1	2	2	3	3	3
8,000 - 9,999	1	1	2	3	3	3	3
6,000 - 7,999	1	2	2	3	3	4	4
5,000 - 5,999	1	2	2	3	3	4	4
4,000 - 4,999	1	2	3	3	3	4	4
3,000 - 3,999	1	2	3	3	3	4	4
2,000 - 2,999	1	2	3	3	4	5	5
1,000 - 1,999	1	3	3	3	4	5	5
500 - 999	1	3	4	4	4	5	5
200 - 499	1	3	4	4	5	5	6
50 - 199	1	3	4	5	5	6	6
0 - 49	1	3	6	6	6	6	6

O. Reg. 366/18, s. 1 (5).

### Application

**2.** (1) This Regulation sets out the minimum standards of repair for highways under municipal jurisdiction for the purpose of clause 44 (3) (c) of the Act. O. Reg. 288/03, s. 1.

(2) REVOKED: O. Reg. 23/10, s. 2.

(3) This Regulation does not apply to Class 6 highways. O. Reg. 239/02, s. 2 (3).

### Purpose

**2.1** The purpose of this Regulation is to clarify the scope of the statutory defence available to a municipality under clause 44 (3) (c) of the Act by establishing maintenance standards which are non-prescriptive as to the methods or materials to be used in complying with the standards but instead describe a desired outcome. O. Reg. 366/18, s. 2.

### MAINTENANCE STANDARDS

### Patrolling

**3.** (1) The standard for the frequency of patrolling of highways to check for conditions described in this Regulation is set out in the Table to this section. O. Reg. 23/10, s. 3 (1); O. Reg. 366/18, s. 3 (2).

(2) If it is determined by the municipality that the weather monitoring referred to in section 3.1 indicates that there is a substantial probability of snow accumulation on roadways, ice formation on roadways or icy roadways, the standard for patrolling highways is, in addition to that set out in subsection (1), to patrol highways that the municipality selects as representative of its highways, at intervals deemed necessary by the municipality, to check for such conditions. O. Reg. 47/13, s. 2; O. Reg. 366/18, s. 3 (2).

(3) Patrolling a highway consists of observing the highway, either by driving on or by electronically monitoring the highway, and may be performed by persons responsible for patrolling highways or by persons responsible for or performing highway maintenance activities. O. Reg. 23/10, s. 3 (1).

(4) This section does not apply in respect of the conditions described in section 10, subsections 11 (0.1) and 12 (1) and section 16.1, 16.2, 16.3 or 16.4. O. Reg. 23/10, s. 3 (1); O. Reg. 366/18, s. 3 (3).

TABLE  
PATROLLING FREQUENCY

Class of Highway	Patrolling Frequency
1	3 times every 7 days
2	2 times every 7 days
3	once every 7 days
4	once every 14 days
5	once every 30 days

O. Reg. 239/02, s. 3, Table; O. Reg. 23/10, s. 3 (2).

### Weather monitoring

**3.1** (1) From October 1 to April 30, the standard is to monitor the weather, both current and forecast to occur in the next 24 hours, once every shift or three times per calendar day, whichever is more frequent, at intervals determined by the municipality. O. Reg. 47/13, s. 3; O. Reg. 366/18, s. 4.

(2) From May 1 to September 30, the standard is to monitor the weather, both current and forecast to occur in the next 24 hours, once per calendar day. O. Reg. 47/13, s. 3; O. Reg. 366/18, s. 4.

**Snow accumulation, roadways**

4. (1) Subject to section 4.1, the standard for addressing snow accumulation on roadways is,

(a) after becoming aware of the fact that the snow accumulation on a roadway is greater than the depth set out in the Table to this section, to deploy resources as soon as practicable to address the snow accumulation; and

(b) after the snow accumulation has ended, to address the snow accumulation so as to reduce the snow to a depth less than or equal to the depth set out in the Table within the time set out in the Table,

(i) to provide a minimum lane width of the lesser of three metres for each lane or the actual lane width, or

(ii) on a Class 4 or Class 5 highway with two lanes, to provide a total width of at least five metres. O. Reg. 47/13, s. 4; O. Reg. 366/18, s. 5 (1).

(2) If the depth of snow accumulation on a roadway is less than or equal to the depth set out in the Table to this section, the roadway is deemed to be in a state of repair with respect to snow accumulation. O. Reg. 47/13, s. 4.

(3) For the purposes of this section, the depth of snow accumulation on a roadway and, if applicable, lane width under clause (1) (b), may be determined in accordance with subsection (4) by a municipal employee, agent or contractor, whose duties or responsibilities include one or more of the following:

1. Patrolling highways.
2. Performing highway maintenance activities.
3. Supervising staff who perform activities described in paragraph 1 or 2. O. Reg. 47/13, s. 4; O. Reg. 366/18, s. 5 (2).

(4) The depth of snow accumulation on a roadway and lane width may be determined by,

- (a) performing an actual measurement;
- (b) monitoring the weather; or
- (c) performing a visual estimate. O. Reg. 47/13, s. 4; O. Reg. 366/18, s. 5 (3).

(5) For the purposes of this section, addressing snow accumulation on a roadway includes,

- (a) plowing the roadway;
- (b) salting the roadway;
- (c) applying abrasive materials to the roadway;
- (d) applying other chemical or organic agents to the roadway;
- (e) any combination of the methods described in clauses (a) to (d). O. Reg. 366/18, s. 5 (4).

(6) This section does not apply to that portion of the roadway,

- (a) designated for parking;
- (b) consisting of a bicycle lane or other bicycle facility; or
- (d) used by a municipality for snow storage. O. Reg. 366/18, s. 5 (4).

TABLE  
SNOW ACCUMULATION - ROADWAYS

Class of Highway	Depth	Time
1	2.5 cm	4 hours
2	5 cm	6 hours
3	8 cm	12 hours
4	8 cm	16 hours
5	10 cm	24 hours

O. Reg. 47/13, s. 4; O. Reg. 366/18, s. 5 (5).

**Snow accumulation on roadways, significant weather event**

4.1 (1) If a municipality declares a significant weather event relating to snow accumulation, the standard for addressing snow accumulation on roadways until the declaration of the end of the significant weather event is,

(a) to monitor the weather in accordance with section 3.1; and

(b) if deemed practicable by the municipality, to deploy resources to address snow accumulation on roadways, starting from the time that the municipality deems appropriate to do so. O. Reg. 366/18, s. 7.

(2) If the municipality complies with subsection (1), all roadways within the municipality are deemed to be in a state of repair with respect to snow accumulation until the applicable time in the Table to section 4 expires following the declaration of the end of the significant weather event by the municipality. O. Reg. 366/18, s. 7.

(3) Following the end of the weather hazard in respect of which a significant weather event was declared by a municipality under subsection (1), the municipality shall,

(a) declare the end of the significant weather event when the municipality determines it is appropriate to do so; and



(b) address snow accumulation on roadways in accordance with section 4. O. Reg. 366/18, s. 7.

### **Snow accumulation, bicycle lanes**

**4.2** (1) Subject to section 4.3, the standard for addressing snow accumulation on bicycle lanes is,

(a) after becoming aware of the fact that the snow accumulation on a bicycle lane is greater than the depth set out in the Table to this section, to deploy resources as soon as practicable to address the snow accumulation; and

(b) after the snow accumulation has ended, to address the snow accumulation so as to reduce the snow to a depth less than or equal to the depth set out in the Table to this section to provide a minimum bicycle lane width of the lesser of 1 metre or the actual bicycle lane width. O. Reg. 366/18, s. 7.

(2) If the depth of snow accumulation on a bicycle lane is less than or equal to the depth set out in the Table to this section, the bicycle lane is deemed to be in a state of repair in respect of snow accumulation. O. Reg. 366/18, s. 7.

(3) For the purposes of this section, the depth of snow accumulation on a bicycle lane and, if applicable, lane width under clause (1) (b), may be determined in the same manner as set out in subsection 4 (4) and by the persons mentioned in subsection 4 (3), with necessary modifications. O. Reg. 366/18, s. 7.

(4) For the purposes of this section, addressing snow accumulation on a bicycle lane includes,

(a) plowing the bicycle lane;

(b) salting the bicycle lane;

(c) applying abrasive materials to the bicycle lane;

(d) applying other chemical or organic agents to the bicycle lane;

(e) sweeping the bicycle lane; or

(f) any combination of the methods described in clauses (a) to (e). O. Reg. 366/18, s. 7.

TABLE  
SNOW ACCUMULATION – BICYCLE LANES

Column 1 Class of Highway or Adjacent Highway	Column 2 Depth	Column 3 Time
1	2.5 cm	8 hours
2	5 cm	12 hours
3	8 cm	24 hours
4	8 cm	24 hours
5	10 cm	24 hours

O. Reg. 366/18, s. 7.

### **Snow accumulation on bicycle lanes, significant weather event**

**4.3** (1) If a municipality declares a significant weather event relating to snow accumulation, the standard for addressing snow accumulation on bicycle lanes until the declaration of the end of the significant weather event is,

(a) to monitor the weather in accordance with section 3.1; and

(b) if deemed practicable by the municipality, to deploy resources to address snow accumulation on bicycle lanes, starting from the time that the municipality deems appropriate to do so. O. Reg. 366/18, s. 7.

(2) If the municipality complies with subsection (1), all bicycle lanes within the municipality are deemed to be in a state of repair with respect to snow accumulation until the applicable time in the Table to section 4.2 expires following the declaration of the end of the significant weather event by the municipality. O. Reg. 366/18, s. 7.

(3) Following the end of the weather hazard in respect of which a significant weather event was declared by a municipality under subsection (1), the municipality shall,

(a) declare the end of the significant weather event when the municipality determines it is appropriate to do so; and

(b) address snow accumulation on bicycle lanes in accordance with section 4.2. O. Reg. 366/18, s. 7.

### **Ice formation on roadways and icy roadways**

**5.** (1) The standard for the prevention of ice formation on roadways is doing the following in the 24-hour period preceding an alleged formation of ice on a roadway:

1. Monitor the weather in accordance with section 3.1.

2. Patrol in accordance with section 3.

3. If the municipality determines, as a result of its activities under paragraph 1 or 2, that there is a substantial probability of ice forming on a roadway, treat the roadway, if practicable, to prevent ice formation within the time set out in Table 1 to this section, starting from the time that the municipality determines is the appropriate time to deploy resources for that purpose. O. Reg. 366/18, s. 8.

(2) If the municipality meets the standard set out in subsection (1) and, despite such compliance, ice forms on a roadway, the roadway is deemed to be in a state of repair until the applicable time set out in Table 2 to this section expires after the municipality becomes aware of the fact that the roadway is icy. O. Reg. 366/18, s. 8.

(3) Subject to section 5.1, the standard for treating icy roadways is to treat the icy roadway within the time set out in Table 2 to this section, and an icy roadway is deemed to be in a state of repair until the applicable time set out in Table 2 to this section expires after the municipality becomes aware of the fact that a roadway is icy. O. Reg. 366/18, s. 8.

(4) For the purposes of this section, treating a roadway means applying material to the roadway, including but not limited to, salt, sand or any combination of salt and sand. O. Reg. 366/18, s. 8.

(5) For greater certainty, this section applies in respect of ice formation on bicycle lanes on a roadway, but does not apply to other types of bicycle facilities. O. Reg. 366/18, s. 8.

TABLE 1  
ICE FORMATION PREVENTION

Class of Highway	Time
1	6 hours
2	8 hours
3	16 hours
4	24 hours
5	24 hours

O. Reg. 366/18, s. 8.

TABLE 2  
TREATMENT OF ICY ROADWAYS

Class of Highway	Time
1	3 hours
2	4 hours
3	8 hours
4	12 hours
5	16 hours

O. Reg. 366/18, s. 8.

### Icy roadways, significant weather event

**5.1** (1) If a municipality declares a significant weather event relating to ice, the standard for treating icy roadways until the declaration of the end of the significant weather event is,

(a) to monitor the weather in accordance with section 3.1; and

(b) if deemed practicable by the municipality, to deploy resources to treat icy roadways, starting from the time that the municipality deems appropriate to do so. O. Reg. 366/18, s. 8.

(2) If the municipality complies with subsection (1), all roadways within the municipality are deemed to be in a state of repair with respect to any ice which forms or may be present until the applicable time in Table 2 to section 5 expires after the declaration of the end of the significant weather event by the municipality. O. Reg. 366/18, s. 8.

(3) Following the end of the weather hazard in respect of which a significant weather event was declared by a municipality under subsection (1), the municipality shall,

(a) declare the end of the significant weather event when the municipality determines it is appropriate to do so; and

(b) treat icy roadways in accordance with section 5. O. Reg. 366/18, s. 8.

### Potholes

**6.** (1) If a pothole exceeds both the surface area and depth set out in Table 1, 2 or 3 to this section, as the case may be, the standard is to repair the pothole within the time set out in Table 1, 2 or 3, as appropriate, after becoming aware of the fact. O. Reg. 239/02, s. 6 (1); O. Reg. 366/18, s. 8 (1).

(1.1) For the purposes of this section, the surface area and depth of a pothole may be determined in accordance with subsections (1.2) and (1.3), as applicable, by a municipal employee, agent or contractor whose duties or responsibilities include one or more of the following:

1. Patrolling highways.

2. Performing highway maintenance activities.

3. Supervising staff who perform activities described in paragraph 1 or 2. O. Reg. 366/18, s. 8 (2).

(1.2) The depth and surface area of a pothole may be determined by,

(a) performing an actual measurement; or

(b) performing a visual estimate. O. Reg. 366/18, s. 8 (2).

(1.3) For the purposes of this section, the surface area of a pothole does not include any area that is merely depressed and not yet broken fully through the surface of the roadway. O. Reg. 366/18, s. 8 (2).

(2) A pothole is deemed to be in a state of repair if its surface area or depth is less than or equal to that set out in Table 1, 2 or 3, as appropriate. O. Reg. 239/02, s. 6 (2); O. Reg. 47/13, s. 6.

TABLE 1  
POTHOLES ON PAVED SURFACE OF ROADWAY

Class of Highway	Surface Area	Depth	Time
1	600 cm <sup>2</sup>	8 cm	4 days
2	800 cm <sup>2</sup>	8 cm	4 days
3	1000 cm <sup>2</sup>	8 cm	7 days
4	1000 cm <sup>2</sup>	8 cm	14 days
5	1000 cm <sup>2</sup>	8 cm	30 days

O. Reg. 239/02, s. 6, Table 1.

TABLE 2  
POTHOLES ON NON-PAVED SURFACE OF ROADWAY

Class of Highway	Surface Area	Depth	Time
3	1500 cm <sup>2</sup>	8 cm	7 days
4	1500 cm <sup>2</sup>	10 cm	14 days
5	1500 cm <sup>2</sup>	12 cm	30 days

O. Reg. 239/02, s. 6, Table 2.

TABLE 3  
POTHOLES ON PAVED OR NON-PAVED SURFACE OF SHOULDER

Class of Highway	Surface Area	Depth	Time
1	1500 cm <sup>2</sup>	8 cm	7 days
2	1500 cm <sup>2</sup>	8 cm	7 days
3	1500 cm <sup>2</sup>	8 cm	14 days
4	1500 cm <sup>2</sup>	10 cm	30 days
5	1500 cm <sup>2</sup>	12 cm	60 days

O. Reg. 239/02, s. 6, Table 3.

### Shoulder drop-offs

**7.** (1) If a shoulder drop-off is deeper than 8 cm, for a continuous distance of 20 metres or more, the standard is to repair the shoulder drop-off within the time set out in the Table to this section after becoming aware of the fact. O. Reg. 366/18, s. 9 (1).

(2) A shoulder drop-off is deemed to be in a state of repair if its depth is less than 8 cm. O. Reg. 366/18, s. 9 (1).

(3) In this section,

“shoulder drop-off” means the vertical differential, where the paved surface of the roadway is higher than the surface of the shoulder, between the paved surface of the roadway and the paved or non-paved surface of the shoulder. O. Reg. 239/02, s. 7 (3).

TABLE  
SHOULDER DROP-OFFS

Class of Highway	Time
1	4 days
2	4 days
3	7 days
4	14 days
5	30 days

O. Reg. 366/18, s. 9 (2).

### Cracks

**8.** (1) If a crack on the paved surface of a roadway is greater than 5 cm wide and 5 cm deep for a continuous distance of three metres or more, the standard is to repair the crack within the time set out in the Table to this section after becoming aware of the fact. O. Reg. 366/18, s. 10 (1).

(2) A crack is deemed to be in a state of repair if its width or depth is less than or equal to 5 cm. O. Reg. 366/18, s. 10 (1).

TABLE  
CRACKS

Column 1 Class of Highway	Column 2 Time
1	30 days
2	30 days
3	60 days
4	180 days
5	180 days

O. Reg. 366/18, s. 10 (2).

### Debris

**9.** (1) If there is debris on a roadway, the standard is to deploy resources, as soon as practicable after becoming aware of the fact, to remove the debris. O. Reg. 239/02, s. 9 (1); O. Reg. 366/18, s. 11.

(2) In this section,

“debris” means any material (except snow, slush or ice) or object on a roadway,

(a) that is not an integral part of the roadway or has not been intentionally placed on the roadway by a municipality, and

(b) that is reasonably likely to cause damage to a motor vehicle or to injure a person in a motor vehicle. O. Reg. 239/02, s. 9 (2); O. Reg. 47/13, s. 9.

### Luminaires

**10.** (0.1) REVOKED: O. Reg. 366/18, s. 12.

(1) The standard for the frequency of inspecting all luminaires to check to see that they are functioning is once per calendar year, with each inspection taking place not more than 16 months from the previous inspection. O. Reg. 366/18, s. 12.

(2) For conventional illumination, if three or more consecutive luminaires on the same side of a highway are not functioning, the standard is to repair the luminaires within the time set out in the Table to this section after becoming aware of the fact. O. Reg. 366/18, s. 12.

(3) For conventional illumination and high mast illumination, if 30 per cent or more of the luminaires on any kilometre of highway are not functioning, the standard is to repair the luminaires within the time set out in the Table to this section after becoming aware of the fact. O. Reg. 366/18, s. 12.

(4) Despite subsection (2), for high mast illumination, if all of the luminaires on consecutive poles on the same side of a highway are not functioning, the standard is to deploy resources as soon as practicable after becoming aware of the fact to repair the luminaires. O. Reg. 366/18, s. 12.

(5) Despite subsections (1), (2) and (3), for conventional illumination and high mast illumination, if more than 50 per cent of the luminaires on any kilometre of a Class 1 highway with a speed limit of 90 kilometres per hour or more are not functioning, the standard is to deploy resources as soon as practicable after becoming aware of the fact to repair the luminaires. O. Reg. 366/18, s. 12.

(6) Luminaires are deemed to be in a state of repair,

(a) for the purpose of subsection (2), if the number of non-functioning consecutive luminaires on the same side of a highway does not exceed two;

(b) for the purpose of subsection (3), if more than 70 per cent of luminaires on any kilometre of highway are functioning;

(c) for the purpose of subsection (4), if one or more of the luminaires on consecutive poles on the same side of a highway are functioning;

(d) for the purpose of subsection (5), if more than 50 per cent of luminaires on any kilometre of highway are functioning. O. Reg. 366/18, s. 12.

(7) In this section,

"conventional illumination" means lighting, other than high mast illumination, where there are one or more luminaires per pole;

"high mast illumination" means lighting where there are three or more luminaires per pole and the height of the pole exceeds 20 metres;

"luminaire" means a complete lighting unit consisting of,

(a) a lamp, and

(b) parts designed to distribute the light, to position or protect the lamp and to connect the lamp to the power supply. O. Reg. 239/02, s. 10 (7).

TABLE  
LUMINAIRES

Class of Highway	Time
1	7 days
2	7 days
3	14 days
4	14 days
5	14 days

O. Reg. 239/02, s. 10, Table.

## Signs

**11.** (0.1) The standard for the frequency of inspecting signs of a type listed in subsection (2) to check to see that they meet the retro-reflectivity requirements of the Ontario Traffic Manual is once per calendar year, with each inspection taking place not more than 16 months from the previous inspection. O. Reg. 23/10, s. 7 (1); O. Reg. 47/13, s. 11 (1); O. Reg. 366/18, s. 13.

(0.2) A sign that has been inspected in accordance with subsection (0.1) is deemed to be in a state of repair with respect to the retro-reflectivity requirements of the Ontario Traffic Manual until the next inspection in accordance with that subsection, provided that the municipality does not acquire actual knowledge that the sign has ceased to meet these requirements. O. Reg. 47/13, s. 11 (2).

(1) If any sign of a type listed in subsection (2) is illegible, improperly oriented, obscured or missing, the standard is to deploy resources as soon as practicable after becoming aware of the fact to repair or replace the sign. O. Reg. 239/02, s. 11 (1); O. Reg. 23/10, s. 7 (2); O. Reg. 366/18, s. 13.

(2) This section applies to the following types of signs:

1. Checkerboard.
2. Curve sign with advisory speed tab.
3. Do not enter.
- 3.1 Load Restricted Bridge.
- 3.2 Low Bridge.
- 3.3 Low Bridge Ahead.
4. One Way.
5. School Zone Speed Limit.
6. Stop.
7. Stop Ahead.
8. Stop Ahead, New.
9. Traffic Signal Ahead, New.
10. Two-Way Traffic Ahead.
11. Wrong Way.

12. Yield.
13. Yield Ahead.
14. Yield Ahead, New. O. Reg. 239/02, s. 11 (2); O. Reg. 23/10, s. 7 (3).

### Regulatory or warning signs

**12.** (1) The standard for the frequency of inspecting regulatory signs or warning signs to check to see that they meet the retro-reflectivity requirements of the Ontario Traffic Manual is once per calendar year, with each inspection taking place not more than 16 months from the previous inspection. O. Reg. 23/10, s. 8; O. Reg. 47/13, s. 12 (1); O. Reg. 366/18, s. 13.

(1.1) A regulatory sign or warning sign that has been inspected in accordance with subsection (1) is deemed to be in a state of repair with respect to the retro-reflectivity requirements of the Ontario Traffic Manual until the next inspection in accordance with that subsection, provided that the municipality does not acquire actual knowledge that the sign has ceased to meet these requirements. O. Reg. 47/13, s. 12 (2).

(2) If a regulatory sign or warning sign is illegible, improperly oriented, obscured or missing, the standard is to repair or replace the sign within the time set out in the Table to this section after becoming aware of the fact. O. Reg. 23/10, s. 8; O. Reg. 366/18, s. 13.

(3) In this section, "regulatory sign" and "warning sign" have the same meanings as in the Ontario Traffic Manual, except that they do not include a sign listed in subsection 11 (2) of this Regulation. O. Reg. 23/10, s. 8.

TABLE  
REGULATORY AND WARNING SIGNS

Class of Highway	Time
1	7 days
2	14 days
3	21 days
4	30 days
5	30 days

O. Reg. 239/02, s. 12, Table.

### Traffic control signal systems

**13.** (1) If a traffic control signal system is defective in any way described in subsection (2), the standard is to deploy resources as soon as practicable after becoming aware of the defect to repair the defect or replace the defective component of the traffic control signal system. O. Reg. 239/02, s. 13 (1); O. Reg. 366/18, s. 13.

(2) This section applies if a traffic control signal system is defective in any of the following ways:

1. One or more displays show conflicting signal indications.
2. The angle of a traffic control signal or pedestrian control indication has been changed in such a way that the traffic or pedestrian facing it does not have clear visibility of the information conveyed or that it conveys confusing information to traffic or pedestrians facing other directions.
3. A phase required to allow a pedestrian or vehicle to safely travel through an intersection fails to occur.
4. There are phase or cycle timing errors interfering with the ability of a pedestrian or vehicle to safely travel through an intersection.
5. There is a power failure in the traffic control signal system.
6. The traffic control signal system cabinet has been displaced from its proper position.
7. There is a failure of any of the traffic control signal support structures.
8. A signal lamp or a pedestrian control indication is not functioning.
9. Signals are flashing when flashing mode is not a part of the normal signal operation. O. Reg. 239/02, s. 13 (2).

(3) Despite subsection (1) and paragraph 8 of subsection (2), if the posted speed of all approaches to the intersection or location of the non-functioning signal lamp or pedestrian control indication is less than 80 kilometres per hour and the signal that is not functioning is a green or a pedestrian "walk" signal, the standard is to repair or replace the defective component by the end of the next business day. O. Reg. 239/02, s. 13 (3); O. Reg. 366/18, s. 13.

- (4) In this section and section 14,
- "cycle" means a complete sequence of traffic control indications at a location;
  - "display" means the illuminated and non-illuminated signals facing the traffic;
  - "indication" has the same meaning as in the *Highway Traffic Act*;
  - "phase" means a part of a cycle from the time where one or more traffic directions receive a green indication to the time where one or more different traffic directions receive a green indication;
  - "power failure" means a reduction in power or a loss in power preventing the traffic control signal system from operating as intended;
  - "traffic control signal" has the same meaning as in the *Highway Traffic Act*;
  - "traffic control signal system" has the same meaning as in the *Highway Traffic Act*. O. Reg. 239/02, s. 13 (4).

### Traffic control signal system sub-systems

**14.** (1) The standard is to inspect, test and maintain the following traffic control signal system sub-systems once per calendar year, with each inspection taking place not more than 16 months from the previous inspection:

1. The display sub-system, consisting of traffic signal and pedestrian crossing heads, physical support structures and support cables.
2. The traffic control sub-system, including the traffic control signal cabinet and internal devices such as timer, detection devices and associated hardware, but excluding conflict monitors.
3. The external detection sub-system, consisting of detection sensors for all vehicles, including emergency and railway vehicles and pedestrian push- buttons. O. Reg. 239/02, s. 14 (1); O. Reg. 47/13, s. 13 (1); O. Reg. 366/18, s. 13.

(1.1) A traffic control signal system sub-system that has been inspected, tested and maintained in accordance with subsection (1) is deemed to be in a state of repair until the next inspection in accordance with that subsection, provided that the municipality does not acquire actual knowledge that the traffic control signal system sub-system has ceased to be in a state of repair. O. Reg. 47/13, s. 13 (2).

(2) The standard is to inspect, test and maintain conflict monitors every five to seven months and at least twice per calendar year. O. Reg. 239/02, s. 14 (2); O. Reg. 47/13, s. 13 (3); O. Reg. 366/18, s. 13.

(2.1) A conflict monitor that has been inspected, tested and maintained in accordance with subsection (2) is deemed to be in a state of repair until the next inspection in accordance with that subsection, provided that the municipality does not acquire actual knowledge that the conflict monitor has ceased to be in a state of repair. O. Reg. 47/13, s. 13 (4).

(3) In this section,

“conflict monitor” means a device that continually checks for conflicting signal indications and responds to a conflict by emitting a signal. O. Reg. 239/02, s. 14 (3).

### Bridge deck spalls

**15.** (1) If a bridge deck spall exceeds both the surface area and depth set out in the Table to this section, the standard is to repair the bridge deck spall within the time set out in the Table after becoming aware of the fact. O. Reg. 239/02, s. 15 (1); O. Reg. 366/18, s. 13.

(2) A bridge deck spall is deemed to be in a state of repair if its surface area or depth is less than or equal to that set out in the Table. O. Reg. 239/02, s. 15 (2); O. Reg. 47/13, s. 14.

(3) In this section,

“bridge deck spall” means a cavity left by one or more fragments detaching from the paved surface of the roadway or shoulder of a bridge. O. Reg. 239/02, s. 15 (3).

TABLE  
BRIDGE DECK SPALLS

Class of Highway	Surface Area	Depth	Time
1	600 cm <sup>2</sup>	8 cm	4 days
2	800 cm <sup>2</sup>	8 cm	4 days
3	1,000 cm <sup>2</sup>	8 cm	7 days
4	1,000 cm <sup>2</sup>	8 cm	7 days
5	1,000 cm <sup>2</sup>	8 cm	7 days

O. Reg. 239/02, s. 15, Table.

### Roadway surface discontinuities

**16.** (1) If a surface discontinuity on a roadway, other than a surface discontinuity on a bridge deck, exceeds the height set out in the Table to this section, the standard is to repair the surface discontinuity within the time set out in the Table after becoming aware of the fact. O. Reg. 23/10, s. 9; O. Reg. 366/18, s. 13.

(1.1) A surface discontinuity on a roadway, other than a surface discontinuity on a bridge deck, is deemed to be in a state of repair if its height is less than or equal to the height set out in the Table to this section. O. Reg. 47/13, s. 15.

(2) If a surface discontinuity on a bridge deck exceeds five centimetres, the standard is to deploy resources as soon as practicable after becoming aware of the fact to repair the surface discontinuity on the bridge deck. O. Reg. 23/10, s. 9; O. Reg. 366/18, s. 13.

(2.1) A surface discontinuity on a bridge deck is deemed to be in a state of repair if its height is less than or equal to five centimetres. O. Reg. 47/13, s. 15.

(3) In this section,

“surface discontinuity” means a vertical discontinuity creating a step formation at joints or cracks in the paved surface of the roadway, including bridge deck joints, expansion joints and approach slabs to a bridge. O. Reg. 23/10, s. 9.

TABLE  
SURFACE DISCONTINUITIES

Class of Highway	Height	Time
1	5 cm	2 days
2	5 cm	2 days
3	5 cm	7 days
4	5 cm	21 days
5	5 cm	21 days

O. Reg. 239/02, s. 16, Table.

## **Sidewalk surface discontinuities**

**16.1** (1) The standard for the frequency of inspecting sidewalks to check for surface discontinuity is once per calendar year, with each inspection taking place not more than 16 months from the previous inspection. O. Reg. 23/10, s. 10; O. Reg. 47/13, s. 16 (1); O. Reg. 366/18, s. 13.

(1.1) A sidewalk that has been inspected in accordance with subsection (1) is deemed to be in a state of repair with respect to any surface discontinuity until the next inspection in accordance with that subsection, provided that the municipality does not acquire actual knowledge of the presence of a surface discontinuity in excess of two centimetres. O. Reg. 47/13, s. 16 (2).

(2) If a surface discontinuity on or within a sidewalk exceeds two centimetres, the standard is to treat the surface discontinuity within 14 days after acquiring actual knowledge of the fact. O. Reg. 366/18, s. 14.

(2.1) REVOKED: O. Reg. 366/18, s. 14.

(3) A surface discontinuity on or within a sidewalk is deemed to be in a state of repair if it is less than or equal to two centimetres. O. Reg. 366/18, s. 14.

(4) For the purpose of subsection (2), treating a surface discontinuity on or within a sidewalk means taking reasonable measures to protect users of the sidewalk from the discontinuity, including making permanent or temporary repairs, alerting users' attention to the discontinuity or preventing access to the area of discontinuity. O. Reg. 366/18, s. 14.

(5) In this section,

"surface discontinuity" means a vertical discontinuity creating a step formation at any joint or crack in the surface of the sidewalk or any vertical height difference between a utility appurtenance found on or within the sidewalk and the surface of the sidewalk. O. Reg. 366/18, s. 14.

## **Encroachments, area adjacent to sidewalk**

**16.2** (1) The standard for the frequency of inspecting an area adjacent to a sidewalk to check for encroachments is once per calendar year, with each inspection taking place not more than 16 months from the previous inspection. O. Reg. 366/18, s. 15.

(2) The area adjacent to a sidewalk that has been inspected in accordance with subsection (1) is deemed to be in a state of repair in respect of any encroachment present. O. Reg. 366/18, s. 15.

(3) For greater certainty, the area adjacent to a sidewalk begins at the outer edges of a sidewalk and ends at the lesser of the limit of the highway, the back edge of a curb if there is a curb and a maximum of 45 cm. O. Reg. 366/18, s. 15.

(4) The area adjacent to a sidewalk is deemed to be in a state of repair in respect of any encroachment present unless the encroachment is determined by a municipality to be highly unusual given its character and location or to constitute a significant hazard to pedestrians. O. Reg. 366/18, s. 15.

(5) If a municipality determines that an encroachment is highly unusual given its character and location or constitutes a significant hazard to pedestrians, the standard is to treat the encroachment within 28 days after making such a determination, and the encroachment is deemed in a state of repair for 28 days from the time of the determination by the municipality. O. Reg. 366/18, s. 15.

(6) For the purpose of subsection (4), treating an encroachment means taking reasonable measures to protect users, including making permanent or temporary repairs, alerting users' attention to the encroachment or preventing access to the area of the encroachment. O. Reg. 366/18, s. 15.

## **Snow accumulation on sidewalks**

**16.3** (1) Subject to section 16.4, the standard for addressing snow accumulation on a sidewalk after the snow accumulation has ended is,

- a) to reduce the snow to a depth less than or equal to 8 centimetres within 48 hours; and
- b) to provide a minimum sidewalk width of 1 metre. O. Reg. 366/18, s. 15.

(2) If the depth of snow accumulation on a sidewalk is less than or equal to 8 centimetres, the sidewalk is deemed to be in a state of repair in respect of snow accumulation. O. Reg. 366/18, s. 15.

(3) If the depth of snow accumulation on a sidewalk exceeds 8 centimetres while the snow continues to accumulate, the sidewalk is deemed to be in a state of repair with respect to snow accumulation, until 48 hours after the snow accumulation ends. O. Reg. 366/18, s. 15.

(4) For the purposes of this section, the depth of snow accumulation on a sidewalk may be determined in the same manner as set out in subsection 4 (4) and by the persons mentioned in subsection 4 (3) with necessary modifications. O. Reg. 366/18, s. 15.

(5) For the purposes of this section, addressing snow accumulation on a sidewalk includes,

- (a) plowing the sidewalk;
- (b) salting the sidewalk;
- (c) applying abrasive materials to the sidewalk;
- (d) applying other chemical or organic agents to the sidewalk; or
- (e) any combination of the methods described in clauses (a) to (d). O. Reg. 366/18, s. 15.

## **Snow accumulation on sidewalks, significant weather event**

**16.4** (1) If a municipality declares a significant weather event relating to snow accumulation, the standard for addressing snow accumulation on sidewalks until the declaration of the end of the significant weather event is,

- (a) to monitor the weather in accordance with section 3.1; and

(b) if deemed practicable by the municipality, to deploy resources to address snow accumulation on sidewalks starting from the time that the municipality deems appropriate to do so. O. Reg. 366/18, s. 15.

(2) If the municipality complies with subsection (1), all sidewalks within the municipality are deemed to be in a state of repair with respect to any snow present until 48 hours following the declaration of the end of the significant weather event by the municipality. O. Reg. 366/18, s. 15.

(3) Following the end of the weather hazard in respect of which a significant weather event was declared by a municipality under subsection (1), the municipality shall,

(a) declare the end of the significant weather event when the municipality determines it is appropriate to do so; and

(b) address snow accumulation on sidewalks in accordance with section 16.3. O. Reg. 366/18, s. 15.

#### **Ice formation on sidewalks and icy sidewalks**

**16.5** (1) Subject to section 16.6, the standard for the prevention of ice formation on sidewalks is to,

(a) monitor the weather in accordance with section 3.1 in the 24-hour period preceding an alleged formation of ice on a sidewalk; and

(b) treat the sidewalk if practicable to prevent ice formation or improve traction within 48 hours if the municipality determines that there is a substantial probability of ice forming on a sidewalk, starting from the time that the municipality determines is the appropriate time to deploy resources for that purpose. O. Reg. 366/18, s. 15.

(2) If ice forms on a sidewalk even though the municipality meets the standard set out in subsection (1), the sidewalk is deemed to be in a state of repair in respect of ice until 48 hours after the municipality first becomes aware of the fact that the sidewalk is icy. O. Reg. 366/18, s. 15.

(3) The standard for treating icy sidewalks after the municipality becomes aware of the fact that a sidewalk is icy is to treat the icy sidewalk within 48 hours, and an icy sidewalk is deemed to be in a state of repair for 48 hours after it has been treated. O. Reg. 366/18, s. 15.

(4) For the purposes of this section, treating a sidewalk means applying materials including salt, sand or any combination of salt and sand to the sidewalk. O. Reg. 366/18, s. 15.

#### **Icy sidewalks, significant weather event**

**16.6** (1) If a municipality declares a significant weather event relating to ice, the standard for addressing ice formation or ice on sidewalks until the declaration of the end of the significant weather event is,

(a) to monitor the weather in accordance with section 3.1; and

(b) if deemed practicable by the municipality, to deploy resources to treat the sidewalks to prevent ice formation or improve traction, or treat the icy sidewalks, starting from the time that the municipality deems appropriate to do so. O. Reg. 366/18, s. 15.

(2) If the municipality complies with subsection (1), all sidewalks within the municipality are deemed to be in a state of repair with respect to any ice which forms or is present until 48 hours after the declaration of the end of the significant weather event by the municipality. O. Reg. 366/18, s. 15.

(3) Following the end of the weather hazard in respect of which a significant weather event was declared by a municipality under subsection (1), the municipality shall,

(a) declare the end of the significant weather event when the municipality determines it is appropriate to do so; and

(b) address the prevention of ice formation on sidewalks or treat icy sidewalks in accordance with section 16.5. O. Reg. 366/18, s. 15.

#### **Winter sidewalk patrol**

**16.7** (1) If it is determined by the municipality that the weather monitoring referred to in section 3.1 indicates that there is a substantial probability of snow accumulation on sidewalks in excess of 8 cm, ice formation on sidewalks or icy sidewalks, the standard for patrolling sidewalks is to patrol sidewalks that the municipality selects as representative of its sidewalks at intervals deemed necessary by the municipality. O. Reg. 366/18, s. 15.

(2) Patrolling a sidewalk consists of visually observing the sidewalk, either by driving by the sidewalk on the adjacent roadway or by driving or walking on the sidewalk or by electronically monitoring the sidewalk, and may be performed by persons responsible for patrolling roadways or sidewalks or by persons responsible for or performing roadway or sidewalk maintenance activities. O. Reg. 366/18, s. 15.

#### **Closure of a highway**

**16.8** (1) When a municipality closes a highway or part of a highway pursuant to its powers under the Act, the highway is deemed to be in a state of repair in respect of all conditions described in this Regulation from the time of the closure until the highway is re-opened by the municipality. O. Reg. 366/18, s. 15.

(2) For the purposes of subsection (1), a highway or part of a highway is closed on the earlier of,

(a) when a municipality passes a by-law to close the highway or part of the highway; and

(b) when a municipality has taken such steps as it determines necessary to temporarily close the highway or part of a highway. O. Reg. 366/18, s. 15.

#### **Declaration of significant weather event**

**16.9.** A municipality declaring the beginning of a significant weather event or declaring the end of a significant weather event under this Regulation shall do so in one or more of the following ways:



1. By posting a notice on the municipality's website.
2. By making an announcement on a social media platform, such as Facebook or Twitter.
3. By sending a press release or similar communication to internet, newspaper, radio or television media.
4. By notification through the municipality's police service.
5. By any other notification method required in a by-law of the municipality. O. Reg. 366/18, s. 15.

#### REVIEW OF REGULATION

##### **Review**

**17.** (1) The Minister of Transportation shall conduct a review of this Regulation and Ontario Regulation 612/06 (Minimum Maintenance Standards for Highways in the City of Toronto) made under the *City of Toronto Act, 2006* every five years. O. Reg. 613/06, s. 2.

(2) Despite subsection (1), the first review after the completion of the review started before the end of 2007 shall be started five years after the day Ontario Regulation 23/10 is filed. O. Reg. 23/10, s. 11.

**18.** OMITTED (PROVIDES FOR COMING INTO FORCE OF PROVISIONS OF THIS REGULATION). O. Reg. 239/02, s. 18.